



## UNIVERSAL DAMP SEALER PRODUCT CODE: DMP00

### TECHNICAL DATA SHEET

APRIL 2024 REVISION 1

---

## PRODUCT DESCRIPTION

Universal Damp Sealer a new generation solvent based solution acrylic waterproofing compound, with white cement to provide a long lasting, seamless and flexible waterproofing

---

## PRODUCT FEATURES AND BENEFITS

The product is seamless and a flexible waterproof coating for rising and lateral damp

Highly water resistant

Excellent adhesion

Can be overcoated with a wide range of Universal Water and Solvent Based Products

---

## PRODUCT INFORMATION

<b>Colour</b>	White
<b>Surface Appearance</b>	Slight Glossy
<b>Resin Base</b>	Solution Acrylic
<b>Solids Content</b>	By volume: Approx.59%
<b>VOC Content</b>	Very High VOC content more than 50%
<b>Spreading Rate</b>	Theoretical Spreading Rate: 11,8m <sup>2</sup> /litre @ 50 µm DFT Practical Spreading Rate: 7,5m <sup>2</sup> /litre @ 50 µm DFT
<b>Recommend WFT &amp; DFT</b>	76 – 93 µm WFT depending on the surface, porosity, profile and application method 45 – 55 µm DFT depending on the surface, porosity, profile and application Method
<b>Pack Sizes</b>	Available in 1ℓ & 5ℓ.



## APPLICATION INFORMATION

<b>Application Conditions</b>	Surface Temperatures at 23°C Relative Humidity 50%
<b>Recoating Time</b>	Allow 24 hours to dry before over coating and must be coated within 72 hours
<b>Application Methods</b>	Brush or short hair roller
<b>Thinner</b>	Ready to use. Do not thin
<b>Cleaning of equipment</b>	Mineral Turpentine

---

## SURFACE PREPARATION

### NEW SURFACES

The substrates must be clean, dry and sound and free of laitance

Apply 1 coat of Universal Damp Sealer allowing 24 hours to dry

Apply 2 coats of any Universal water based or solvent based top coats

### PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound.

Remove all loose, flaking and bubbling paint.

Remove all dust, foreign material, fungal and algae growth.

Repair cracks with the appropriate crack interior and exterior fillers.

Apply 1 coat of Universal Damp Sealer allowing 24 hours to dry.

Apply 2 coats of any Universal water based or solvent based top coats.

---

## PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product is lead free, contains very high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

Empty containers are suitable for recycling. But caution must be exercised in the disposal of used containers

---

## DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application

