



UNIVERSAL PINKWOOD PRIMER PRODUCT CODE: PRIPNK
TECHNICAL DATA SHEET
APRIL 2024 REVISION 1

PRODUCT DESCRIPTION

Universal Pinkwood Primer is an alkyd/oil based primer which has been formulated with oil to feed and nourish wood

PRODUCT FEATURES AND BENEFITS

For interior and exterior on wood

Excellent adhesion

Excellent application properties

High hiding power and film build

Easy to apply with brush or roller

Can be overcoated with a wide range of Universal Water and Solvent Based Products

PRODUCT INFORMATION

Colour	Pink
Surface Appearance	Low Sheen
Resin Base	Alkyd Based
Solids Content	By volume: Approx. 77%
VOC Content	High VOC content 25% to 50%
Spreading Rate	Theoretical Spreading Rate: 19m ² /litre @ 40 µm DFT Practical Spreading Rate: 11,2m ² /litre @ 40 µm DFT
Recommend WFT & DFT	46-58 µm WFT depending on the surface porosity, profile and application method 35-45 µm DFT depending on the surface porosity, profile and application Method
Pack Sizes	Available in 1ℓ & 5ℓ .



APPLICATION INFORMATION

Application Conditions	Surface Temperatures at 23°C Relative Humidity 50%
Recoating Time	16 hours drying time before over coating
Application Methods	Brush
Thinner	Is ready for use, do not thin
Cleaning of equipment	Universal Mineral Turpentine

SURFACE PREPARATION

NEW SURFACES

The substrates must be clean, dry and sound and free of contaminants.

Apply one coat of Universal Pinkwood Primer allowing 16 hours drying time.

The entire surface can now be coated with 2 coats of Universal water based or solvent based top coat.

PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound

Remove all loose and flaking paint

Remove all dust, foreign material, fungal and algae growth, which is to be treated with Universal Fungal Wash

All knots and cracks to be sealed

Spot prime using Universal Pinkwood Primer to the bare and repair areas then apply one coat Universal Pinkwood Primer to the entire surface. Allowing 16 hours drying time

The entire area can now be coated with 2 coats of Universal water based or solvent based top coat

PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product is lead free, contains very high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

Empty containers are suitable for recycling. But caution must be exercised in the disposal of used containers

DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application