



**UNIVERSAL PINKWOOD PRIMER** PRODUCT CODE: PRIPNK  
TECHNICAL DATA SHEET  
JULY 2019 REVISION 4

---

**PRODUCT DESCRIPTION**

Universal Pinkwood Primer is an alkyd/oil based primer which has been formulated with oil to feed and nourish wood

---

**PRODUCT FEATURES AND BENEFITS**

For interior and exterior on wood

Excellent adhesion

Excellent application properties

High hiding power and film build

Easy to apply with brush or roller

Can be overcoated with a wide range of Universal Water and Solvent Based Products

---

**PRODUCT INFORMATION**

<b>Colour</b>	Pink
<b>Surface Appearance</b>	Low Sheen
<b>Resin Base</b>	Alkyd Based
<b>Solids Content</b>	By volume: Approx. 77%
<b>VOC Content</b>	High VOC content 25% to 50%
<b>Spreading Rate</b>	Theoretical Spreading Rate: 19m <sup>2</sup> /litre @ 40 µm DFT Practical Spreading Rate: 11,2m <sup>2</sup> /litre @ 40 µm DFT
<b>Recommend WFT &amp; DFT</b>	46-58 µm WFT depending on the surface porosity, profile and application method 35-45 µm DFT depending on the surface porosity, profile and application Method
<b>Pack Sizes</b>	Available in 1ℓ & 5ℓ .

---



## APPLICATION INFORMATION

<b>Application Conditions</b>	Surface Temperatures at 23°C Relative Humidity 50%
<b>Recoating Time</b>	16 hours drying time before over coating
<b>Application Methods</b>	Brush
<b>Thinner</b>	Is ready for use, do not thin
<b>Cleaning of equipment</b>	Universal Mineral Turpentine

## SURFACE PREPARATION

### NEW SURFACES

The substrates must be clean, dry and sound and free of contaminants.

Apply one coat of Universal Pinkwood Primer allowing 16 hours drying time.

The entire surface can now be coated with 2 coats of Universal water based or solvent based top coat.

### PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound

Remove all loose and flaking paint

Remove all dust, foreign material, fungal and algae growth, which is to be treated with Universal Fungal Wash

All knots and cracks to be sealed

Spot prime using Universal Pinkwood Primer to the bare and repair areas then apply one coat Universal Pinkwood Primer to the entire surface. Allowing 16 hours drying time

The entire area can now be coated with 2 coats of Universal water based or solvent based top coat

---

## PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product contains high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

---

## DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application