



UNIVERSAL ACRYLIC CRACK FILLER PRODUCT CODE: ACR00
TECHNICAL DATA SHEET
JULY 2019 REVISION 4

PRODUCT DESCRIPTION

Universal Acrylic Crack Filler is a versatile water based crack-patching compound for filling cracks and holes for exterior and interior walls.

PRODUCT FEATURES AND BENEFITS

For interior and exterior to seal vertical and horizontal cracks on plaster cement walls (up to a maximum of 3 mm)

Provides excellent flexibility and durability

High water resistance with a low water pick up

PRODUCT INFORMATION

Colour	Off-white
Surface Appearance	matt
Resin Base	Acrylic Emulsion
Solids Content	n/a
VOC Content	n/a
Spreading Rate	fill cracks up to 3mm
Recommend WFT & DFT	n/a
Pack Sizes	Available in 1ℓ, 5ℓ & 20ℓ

APPLICATION INFORMATION

Application Conditions	Surface Temperatures at 23°C Relative Humidity 50%
Recoating Time	24 hours to dry before over coating
Application Methods	Utilise a spatula, scraper or trowel
Thinner	Is ready for use, not to be thinned
Cleaning of equipment	Water



SURFACE PREPARATION

NEW AND PREVIOUSLY COATED SURFACES & WALLS

The substrates must be clean, dry, sound and free of any contaminants

All cracks to be “V” out when opening them

Smooth product within 30 minutes of application

Spot prime using Universal Water Based Primer (allowing 4 hours to dry) or Universal Pigmented Primer (allow 16 hours to dry) or Universal Bonding Liquid (allowing 24 hours to dry however it must be overcoated within 72 hours) to all bare and repaired areas

Apply 2 coats of any Universal water-based or solvent based top coats

PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Over time the cracks have a tendency to reopen.

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application