



UNIVERSAL ALLWOOD PRODUCT CODE: ALW00

TECHNICAL DATA SHEET

JULY 2019 REVISION 4

PRODUCT DESCRIPTION

Universal Allwood is manufactured using low viscosity long oils blended with selected linseed oils and UV absorbers.

PRODUCT FEATURES AND BENEFITS

For exterior sanded wooden window frames, wooden doors and frames, skirting's and garden furniture

Life expectancy of at least 1-2 years

Highly durable

UV resistant

PRODUCT INFORMATION

Colour	Clear
Surface Appearance	Gloss or Matt finish
Resin Base	Alkyd
Solids Content	By volume: Approx. 41%
VOC Content	Very High VOC content more than 50%
Spreading Rate	Theoretical Spreading Rate: 13,7m ² /litre @ 30 µm DFT Practical Spreading Rate: 7,5m ² /litre @ 30 µm DFT
Recommend WFT & DFT	61 – 85 µm WFT depending on the surface, porosity, profile and application method 25 – 35 µm DFT depending on the surface, porosity, profile and application Method
Pack Sizes	Available in 1ℓ & 5ℓ

APPLICATION INFORMATION

Application Conditions	Surface Temperatures at 23°C Relative Humidity 50%
Recoating Time	12 hours to dry before over coating
Application Methods	Brush or Roller
Thinner	Is ready for use, do not thin.
Cleaning of equipment	Universal Mineral Turpentine



SURFACE PREPARATION

NEW SURFACES WOOD

The substrates must be clean, dry and sound and free of any contaminants

Machine Sand or hand sand in direction of grain using 100 – 150 grit paper

Dust off

Apply 3 coats Universal Allwood allowing 12 hours to dry between coats

PREVIOUSLY COATED SURFACES WOOD

The substrates must be clean, dry and sound and free of any contaminants

Remove all loose and flaking paint and sand existing coating

Machine Sand or hand sand in direction of grain using 100 – 150 grit paper

Dust off

Apply 3 coats Universal Allwood allowing 12 hours to dry between coats

PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product contains very high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application

