



UNIVERSAL DAMP SEALER PRODUCT CODE: DMP00

TECHNICAL DATA SHEET

JULY 2019 REVISION 4

PRODUCT DESCRIPTION

Universal Damp Sealer a new generation solvent based solution acrylic waterproofing compound, with white cement to provide a long lasting, seamless and flexible waterproofing

PRODUCT FEATURES AND BENEFITS

The product is seamless and a flexible waterproof coating for rising and lateral damp

Highly water resistant

Excellent adhesion

Can be overcoated with a wide range of Universal Water and Solvent Based Products

PRODUCT INFORMATION

Colour	White
Surface Appearance	Slight Glossy
Resin Base	Solution Acrylic
Solids Content	By volume: Approx.59%
VOC Content	Very High VOC content more than 50%
Spreading Rate	Theoretical Spreading Rate: 11,8m ² /litre @ 50 µm DFT Practical Spreading Rate: 7,5m ² /litre @ 50 µm DFT
Recommend WFT & DFT	76 – 93 µm WFT depending on the surface, porosity, profile and application method 45 – 55 µm DFT depending on the surface, porosity, profile and application Method
Pack Sizes	Available in 1ℓ & 5ℓ.



APPLICATION INFORMATION

Application Conditions	Surface Temperatures at 23°C Relative Humidity 50%
Recoating Time	Allow 24 hours to dry before over coating and must be coated within 72 hours
Application Methods	Brush or short hair roller
Thinner	Ready to use. Do not thin
Cleaning of equipment	Mineral Turpentine

SURFACE PREPARATION

NEW SURFACES

The substrates must be clean, dry and sound and free of laitance

Apply 1 coat of Universal Damp Sealer allowing 24 hours to dry

Apply 2 coats of any Universal water based or solvent based top coats

PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound.

Remove all loose, flaking and bubbling paint.

Remove all dust, foreign material, fungal and algae growth.

Repair cracks with the appropriate crack interior and exterior fillers.

Apply 1 coat of Universal Damp Sealer allowing 24 hours to dry.

Apply 2 coats of any Universal water based or solvent based top coats.

PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product contains very high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application