



## UNIVERSAL PIGMENTED PLASTER PRIMER PRODUCT CODE: PPL00

### TECHNICAL DATA SHEET

JULY 2019 REVISION 4

---

### PRODUCT DESCRIPTION

Universal Pigmented Plaster Primer is a classical solvent-based primer

---

### PRODUCT FEATURES AND BENEFITS

For interior and exterior on Cement Plaster, Concrete, Gypsum Plaster, Rhinolite, Fibre Cement, Chipboard and Hardboard

Serves as both a sealer and a primer

Excellent adhesion

Excellent application properties

High Alkali Barrier, high hiding power and film build

Easy to apply with brush or roller

Can be overcoated with a wide range of Universal Water and Solvent Based Products

---

### PRODUCT INFORMATION

|                                |   |
|--------------------------------|---|
| <b>Colour</b>                  | White or Opaque Liquid  |
| <b>Surface Appearance</b>      | Low sheen   |
| <b>Resin Base</b>              | Thermoplastic Polymer   |
| <b>Solids Content</b>          | By volume: Approx.56%   |
| <b>VOC Content</b>             | High VOC content 25% to 50%   |
| <b>Spreading Rate</b>          | Theoretical Spreading Rate: 11,4m <sup>2</sup> /litre @ 35 µm DFT<br>Practical Spreading Rate: 6,5m <sup>2</sup> /litre @ 35 µm DFT                                   |
| <b>Recommend WFT &amp; DFT</b> | 75 – 100 µm WFT depending on the surface porosity, profile and application method<br>30 – 40 µm DFT depending on the surface porosity, profile and application Method |
| <b>Pack Sizes</b>              | Available in 1ℓ, 5ℓ & 20ℓ.  |

---



## APPLICATION INFORMATION

|                               |   |
|-------------------------------|---|
| <b>Application Conditions</b> | Surface Temperatures at 23°C<br>Relative Humidity 50% |
| <b>Recoating Time</b>         | 16 hours to dry before over coating                   |
| <b>Application Methods</b>    | Brush or roller or airless spray                      |
| <b>Thinner</b>                | Is ready for use, do not thin                         |
| <b>Cleaning of equipment</b>  | Universal Mineral Turpentine                          |

## SURFACE PREPARATION

### NEW SURFACES

The substrates must be clean, dry and sound and free of contaminants.

Apply one coat of Universal Pigmented Plaster Primer.

The entire surface can now be coated with a Universal water based or solvent based top coat.

### PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound.

Remove all loose and flaking paint.

Remove all dust, foreign material, fungal and algae growth, which is to be treated with Universal Fungal Wash.

Fill and seal all visible cracks with Universal Paints Acrylic Crack Filler (not more than 3mm).

Spot prime using Universal Pigmented Plaster Primer to the bare and repair areas then apply one coat Universal Pigmented Plaster Primer to the entire surface.

The entire area can now be coated with 2 coats of Universal water based or solvent based top coat

---

## PRECAUTIONS

For detailed safety information please refer to Material Safety Data Sheet

Keep out of reach of children, flames and sparks

This product contains high levels of VOC

Only use in well ventilated areas and do not eat, drink or smoke whilst using this product

---

## DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application