



UNIVERSAL WATER-BASED PLASTER PRIMER PRODUCT CODE: WBP00

TECHNICAL DATA SHEET

JULY 2019 REVISION 4

PRODUCT DESCRIPTION

Universal Water-Based Plaster Primer is suitable for a range of plastered and concrete surfaces.

PRODUCT FEATURES AND BENEFITS

For interior and exterior on Cement Plaster, Concrete, Gypsum Plaster, Rhinolite, Fibre Cement and paper face board

Serves as both a sealer and a primer

Excellent adhesion, save for plastic substrates

Excellent application properties

High Alkali Barrier

Easy to apply with brush or roller

Can be overcoated with a wide range of Universal Water and Solvent Based Products

PRODUCT INFORMATION

| | |
|--------------------------------|--|
| Colour | White / Opaque Liquid |
| Surface Appearance | Matt |
| Resin Base | Pure Acrylic |
| Solids Content | By volume: Approx.31% |
| VOC Content | Minimal VOC content 0% to 0,29% |
| Spreading Rate | Theoretical Spreading Rate: 6,9m ² /litre@ 45 µm DFT Practical Spreading Rate: 4,1m ² /litre @ 45 µm DFT |
| Recommend WFT & DFT | 129-161 µm WFT depending on the surface, porosity, profile and application Method 40-50 µm DFT depending on the surface, porosity, profile and application Method |
| Pack Sizes | Available in 1ℓ, 5ℓ & 20ℓ. |



APPLICATION INFORMATION

| | |
|-------------------------------|---|
| Application Conditions | Surface Temperatures at 23°C Relative Humidity 50% |
| Recoating Time | 4 hours to dry before over coating |
| Application Methods | Brush or roller or airless spray |
| Thinner | Is ready for use, do not thin |
| Cleaning of equipment | Rinse thoroughly with warm water |

SURFACE PREPARATION

NEW SURFACES

The substrates must be clean, dry and sound and free of contaminants.

Apply one coat of Universal Water-Based Plaster Primer allowing 4 hours to dry .

The entire surface can now be coated with a Universal water based or solvent based top coat.

PREVIOUSLY COATED SURFACES

The substrates must be clean, dry and sound

Remove all loose and flaking paint

Remove all dust, foreign material, fungal and algae growth, which is to be treated with Universal Fungal Wash, then apply one coat of Universal Galvanised Prime

Spot prime using Universal Water-Based Plaster Primer to the bare and repair areas then apply one coat Universal Water-Based Plaster Primer to the entire surface allowing 4 hours to dry

The entire area can now be coated with a Universal water based or solvent based top coat

PRECAUTIONS

For detailed safety information please refer to Safety Data Sheet

This product is does not contain any toxic substances and contains minimal levels of VOC

This product is non-flammable

DISCLAIMER

Universal Paints cannot be held liable if the product fails due to improper surface preparation or application