



SAFETY DATA SHEET

DATA SHEET REV 1 OF 2022

UQD/W07

1 PRODUCT IDENTIFICATION AND COMPANY NAME

Product Name	:	Universal Paints Classic Acrylic White
Product Identification	:	Air Drying Emulsion Paint
Supplier/Manufacturer	:	Universal Coatings (Pty) Ltd
Address	:	17 Staal Street, Kya Sands, Randburg, South Africa
Contact	:	R. Diab, G. Murchie
Tel	:	(+27) 11 462 4284

2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Class	:	Emulsion Based Paint
Classification	:	Not Classed as hazardous
R Phrases	:	None
S Phrases	:	S2, 24/25
Hazardous Components	:	No significant quantity of any classified hazardous substance present.

3 HAZARDS IDENTIFICATION

SAPMA Health Rating	:	4-Minimal – No great risk to health.
Human Health Hazards	:	<i>Inhalation:</i> Avoid exposure to vapours, fumes and mists <i>Eyes:</i> May cause slight irritation, any possible contact to be avoided. <i>Ingestion:</i> May cause irritation and nausea <i>Skin:</i> No hazard expected if used in moderation, direct contact to be avoided.
Environmental Hazards	:	No records of chronic effects found, so considered low hazard. Non-toxic but can have undesirable environmental side effects so a lot of care must be taken with disposal.

4 FIRST AID MEASURES

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	:	Move to a safe area with fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
Eye Contact	:	Rinse thoroughly with water for at least 10 minutes. Seek medical attention.
Ingestion	:	Do not induce vomiting. Keep person warm and at rest. Seek medical advice immediately and show the container or label.
Skin Contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use a recognized skin cleanser. Do not use solvents or thinners.

Continued on next page...

5 FIRE-FIGHTING MEASURES

- * This paint is NOT flammable but the dry residue is combustible.
- * Expect no direct explosion hazard. Use CO2, dry powder or foam.

6 ACCIDENTAL RELEASE MEASURES-also see sections 5.8 and 13

Personal Precautions	:	Ventilate the area. Avoid breathing in vapors.
Spill	:	Contain and collect spillage with absorbent material. Dispose of according to local regulations. Do not allow spillage to enter sewerage drains or watercourses.

7 HANDLING AND STORAGE - General - This is inert with no special requirements for hazard containment

Handling	:	Keep container tightly closed. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. After handling the material, workers should wash hands and face before eating, drinking and smoking. Always comply with health and safety regulations.
Storage	:	Store in original container. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from oxidizing agents, strong alkaline and acids. No smoking. Containers which have been opened must be carefully resealed and kept upright to prevent leakage.

8 EXPOSURE CONTROL/PERSONAL PROTECTION

SAPMA Rating	:	4-H-C
Personal Protective Equipment Respiration	:	Should ventilation be inadequate or if workers are exposed to concentrations above the exposure limit, appropriate certified respirators must be used.
Eyes	:	Use safety eyewear designed to protect against splash of liquids. Never touch eyes with dirty hands or gloves.
Ingestion	:	Observe the rules of hygiene. Wash hands and face before eating, drinking or smoking.
Skin	:	Use protective gloves. Wash in case of contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Viscous Opaque Liquid
Flash Point (° Celsius)	:	Not flammable-N/A
Dilution/Wash up	:	Water
Density	:	1.15 - 1.35
pH	:	8.5 - 9.5